

# PAGELynx Lite

**P**AGELynx Lite is a low cost, stand alone paging system that enables messages to be dispatched via an PC style keyboard. In addition to providing quick and easy-to-use messaging PAGELynx Lite may also monitor third party alarm systems.

## **Applications**

PAGELynx Lite is the ideal solution for locating and instructing staff that are continuously on the move. Typical users include; hotels and motels, schools, churches, retail, health care facilities and manufacturing plants.

PAGELynx Lite is perfect for any company that requires the ability to contact staff that are mobile and doesn't want to spend thousands of dollars every year in mobile communication bills.

By utilising an internal transmitter you may send an unlimited number of messages *free of charge*<sup>1</sup>. After the initial purchase there are no monthly access fees or per call charges. Messages are delivered instantly and each recipient receives a detailed set of instructions.

## **Keyboard Paging**

PAGELynx Lite incorporates a two line, backlit LCD display enabling operators to type in messages in the same method as an electronic typewriter - except the message instantly appears on the selected pager(s).

Sending messages is as simple as selecting which pager is to receive the message and typing in the message that you want to be displayed.

## **Alarm Monitoring**

PAGELynx Lite incorporates the facility to monitor alarm conditions via RS232 or hard wired inputs. For example PAGELynx Lite could monitor a fire alarm system. When the fire panel detects a fire then PAGELynx Lite could contact all pagers and alert them to the emergency condition.



## TECHNICAL SPECIFICATIONS

Recipient capacity	1,000 Pagers
Alarm capacity	16 Alarm inputs
Input method	Contact Closure Opto coupled
Alarm configuration	Full alarm escalation
Alert method	Internal pizzo buzzer
Serial ports	1 x RS232C Serial port
Supported protocols	POCSAG 512bps TAP / PET / IXO Free Text Interface
Transmitter	Internal 4 Watt
Frequency range	138-170, 450-470Mhz
Programming	Via in built keyboard
Dimensions	84 x 360 x 220 mm 3.3" x 14.2" x 8.7" inches
Weight	2.575 kg / 5lb 10oz
Power requirements	13.8V at 1.2 amps

<sup>1</sup>Some countries require annual radio licences.

<http://www.commtechwireless.com>

## **Australia**

PO Box 1037  
OPDC WA 6916  
Phone +61 8 9244 5550  
Fax +61 8 9244 5559  
Email [sales@commtech.com.au](mailto:sales@commtech.com.au)

**CommtechWireless**  
[www.commtechwireless.com](http://www.commtechwireless.com)

## **United States**

6900 Philips Highway, Suite #26-27  
JACKSONVILLE FL 32216  
Phone +1 904 281 0073  
Fax +1 904 281 0074  
Email [sales@commtechwireless.com](mailto:sales@commtechwireless.com)